

A professional with spring flap segments!

TUCHEL-SNOW
SK-F

for
small tractors,
yard loaders,
wheel loaders,
fork-lifts
& communal
vehicles



TUCHEL
MASCHINENBAU GmbH

Free of snow in a flash

Standard equipment of the **SK-F** snow blade incl. anti-icing spring flap segments, PU-coated lip (polyurethane), mechanical angling and height adjustable wheels. On option, Tichel offer a highly wear resistant communal- and a steel lip. The optimum angle of inclination ensures perfect and easy snow clearing. Edge bending (side and top) makes the **SK-F** even stronger and much more stable. Various hitch systems for small tractors, yard loaders, fork-lifts and small communal vehicles complete the **SK-F** snow blade. Interceptors (right/left) protect the machine against damage.

technical data		150	180	200	225
total width	cm	150	180	200	225
clearing width (in straight & angled position)	cm	150/ 132	180/ 154	200/ 176	225/ 198
weight*	kg	205	225	240	255
height	cm	70			
angling	degree	up to 30			

* without hitch system

Measurements and weights are approx. and non-binding.

options

- hydraulic angling (1 additional double-acting hydraulic drive circuit required); on demand incl. pressure limit valve
- extra stable, reinforced wheels (ø 200 x 50 mm)
- road traffic equipment (warning flags & -holders, side-marker lamps LED)
- colour option

hitch systems

- Three-point linkage
- A-frame
- Attachment plate for communal vehicles
- Fork-tine attachment
- Yard loader-/ wheel loader hitch incl. levelling (for small wheel loaders)

The main features at a glance:

- interceptors on both sides included in standard equipment
- spring flap segments (anti-icing)
- optimum angle of inclination of the clearing lip, for perfect snow clearing
- edge bending (side and top) ensures high stability of the snow blade



wheels incl. infinitely variable height adjustment



Three-point attachment



spring flap segments (anti-icing)



edge bending (side and top)