That runs like clockwork!



for small tractors, unimogs & fork-lifts









With this you'll get everywhere!

The **VARIO** snow plow is the ideal machine for a flexible clearing of snow. Hydraulic angling, secured by nitrogen bubbles, allows to use the two-part snow plow in V-, Y- and straight position. The PU-coated (polyure-thane) spring flap segments provide security and protect the machine against damage. Height adjustable wheels assure clearing without leaving any marks on road surfaces. Various hitch systems allow a perfect attachment onto your carrier-vehicle.

technical data	150	180	210	260	320	370
clearing width in straight position cm	150	179	218	268	318	368
clearing width in V- shape cm	135	161	199	226	273	281
clearing width in Y- shape cm	135	160	193	222	257	320
plow height middle/side cm	64/ 73	64/ 73	77/ 91	77/ 93	77/ 96	83/ 97
angling rear/front degree	28/ 27	28/ 27	26/ 28	34/ 34	32 /36	41/ 30
weight* kg	254	278	362	435	518	598

^{*} without hitch system, incl. PU-lip and pivoting part (levelling)

options

- Electro-magnetic switch for carrier-vehicles with one double-acting hydraulic drive circuit, only
- Level compensation
- Skids
- Extra strong wheels (200 x 80 mm, steel-welded from 260 cm ø 310 x 105 mm)
- Road traffic equipment (warning flags & -holders, side-marker lamps LED)
- Colour option

hitch systems

- Three-point linkage
- A-frame
- Attachment plate incl. lifting-device
- Fork-tine attachment
- Yard loader-/wheel loader hitch incl. levelling (for small wheel loaders)

The main features at a glance:

- Spring flap segments (anti-icing)
- Optimum angle of inclination of the clearing lip, for perfect snow clearing
- Edge bending (side and top) ensures high stability of the snow plow
- Besides the PU-lip (polyurethane) a highly wear resistant lip incl. corundum inlay can be offered



Spring flap segments (anti-icing)



Hydraulic angling of the folding wings



Interceptors on both sides



VARIO incl. road traffic equipment (flags and lights)