

Effective weed removal!

TUCHEL-SWEEP

WB 750

For
wheel loaders,
tractors, yard
loaders, fork-lifts,
small communal
vehicles & excava-
tors up to 6 t



TUCHEL
MASCHINENBAU GmbH

Environmentally friendly and thoroughly!

The new hydraulically driven weed brush for wheel loaders, tractors, small communal vehicles and excavators allows you to remove any kind of weed, very easy and effortless, and free of chemicals.

The disc brush has a diameter of 750 mm and is equipped with flat wire bunches, so that even stubborn dirt is no longer an obstacle.

To ensure removal even in edge areas, the weed brush is equipped with a mechanical lateral displacement.

Through manually adjusting the tilt angle, you can achieve the highest possible scratch effect.

Part of the basic equipment is also an adjustable rubber protection cloth which prevents stones and debris flying around uncontrollably.

Technical data		
Disc brush \varnothing	mm	750
Brush type		Flat wire bunches
Direction of rotation		right / left
Motor		Danfoss OMS Hydr.-Motor
Required oil flow		20 l / min at 180 bar
Lateral displacement (not for excavators)		Mechanical by 450 mm
Rubber protection cloth		Included

Measurements and weights are approx. and non-binding.

Options

- Rope wire bunches, plastic covered, screwable
- Hydr. inclination adjustment of the brush (1 additional double-acting control circuit necessary)
- Hydr. lateral displacement by 450 mm (1 additional double-acting control circuit necessary)
- Guide wheel / support wheel \varnothing 200 x 50 mm (for < 0,4 m³ bucket capacity)
- Extra strong castor for guide wheel \varnothing 250 x 80 mm (for > 0,4 m³ bucket capacity)
- Throttle valve for speed regulation
- Electro-magnetic switching 12 V, for vehicles with only one double-acting hydraulic control circuit
- Electro-magnetic switching 12 V, for vehicles with two double-acting hydraulic control circuits
- Extra colour shade
- Hydro Drive for vehicles without sufficient oil capacity for (oil tank with approx 55 liters volume)

Hitch systems

- Quick-hitch MS01 / MS03 for mini excavators with max. operating weight up to 6 t
- Three-point linkage CAT I / II
- A-frame CAT Communal / 0 / I
- Yard loader attachment system
- Wheel loader attachment system (up to 0,8 m³ bucket capacity)
- Attachment system for communal vehicles
- Attachment system for fork-lifts



Height adjustable support wheel

Plastic covered rope wire bunches

Telescopic, with hydr. inclination adjustment

Hydro Drive